

AT 52 - Wheel Change Truck

Regular Cab, Dual Rear Wheel 6x4 Chassis,
269" WV, 159" CT, 150" AF
21,600 lb. Payload
56,000 lb. GVWR
80,000 lb. GCWR

Picture Currently
Unavailable

Factory Equipment

- 335 HP 6 Cylinder Diesel Engine
- Front PTO provision, (crank shaft driven pump required)
- Engine Exhaust Brake
- Fuller RTO11908LL 10-speed Manual Transmission
- Standard cab plus 6" (for longer seat travel)
- Power Steering
- Air Brakes with Dual Heated Air Dryers
- Air Lines to End of Frame
- 16,000 lb. Set-Back Front Axle, 40,000 lb. Tandem Rear Axle
- Hendrickson HN-402 Rear Suspension
- Front Spare Tire and Wheel
- HD Frame w/ Reinforcement & Front Frame Ext., Front Tow Hooks
- Full Gauges, Tachometer & Hourmeter
- Block Heater
- Heated Fuel/Water Separator
- 31.0 CFM Air Compressor
- Engine Warning & Shutdown System
- HD Alternator, HD Batteries, Circuit Breakers
- Dual 50 Gallon Fuel Tanks
- Vertical Exhaust, Single
- Tinted Glass
- Air Conditioning
- AM/FM Stereo Radio
- Adjustable Steering Column
- Cigar Lighter
- Headlamps On Warning Buzzer
- Dual Air Horns
- Individual Air Suspended Seats (2), Hi-Back with Arm Rests
- Dual West Coast Heated Mirrors plus 8" convex
- Pedestrian Window in Passenger Door

Factory Options (State on order if required)

- Fuller RTAO-14710C-AS 10-speed Automatic
- Winter front
- 385/65R-22.5J front tires on 12.25" wheels - for vehicles to be operated primarily in states which have 600lb/in restrictions on tire loading (MT, ID, WA, OR, NV, UT)

Equipment Options (State on order if required)

- AT 6C 25 Ton Capacity Towing Package with 7 Prong Receptacle and Electric Brake Controller
- AT 6D Glad Hand Connections for Pulling Air Brake Trailer (See Truck Accessories)
- AT 7D Insulated Hydraulic Rail Gear with Steel Wheels, Front Brakes, 4 Driving Lights, Access Steps to Cab. Includes Reversing Transmission with Automatic Transmission
- AT 10R1 Radio Remote Control
- AT 10W Crane Mounted Winch

Standard Equipment

- Auto Truck 17'L x 8'W Steel Wheel Change Body with Vertical, Horizontal and Under Body Compartments on Both Sides, Gas Bottle Compartment (Passenger Side), Oxygen-Acetylene Hose Reel with 90' of 3/8" T Grade Hose, Driver's Side Compartment 3 Drawers, Master Locking System Long Bar Storage, Axle Rack, Blocking Box, Steps/Stairs, Rear Bumper
- Taillights, backup lights and two floodlights must be recessed into the bumper.
- All cutouts must be covered by steel mesh.
- 70 CFM PTO driven Compressed Air System For Rail Car Test System, Spring Rewind Hose Reel
- 4 Magnetic Work Lights with 4 Outlets
- 8 Work Lights
- Hummingbird Backup Alert Operator Warning System
- Air Shift PTO Hydraulic System w/ Two Spring Rewind Hose Reels
- Miller Diesel Bobcat 250DNT Welder with Canvas Cover, Spring Rewind Reels for 35' Leads and Fuel Lines from Truck Tank
- Electric Cable Reel with 50' of 10/3 Cable
- National N85-H21 Articulating Hydraulic Crane with Capacity of 14,400 lbs @ 6' 3"; 3,000 lbs @ 25' 1"
- Hydraulic Extension to 21' and Manual Extension to 25' 1"; Hydraulic Down & Out Outriggers
- Hydraulic Car Jacking System with Cordless Remote Control, Hose Reels with 75' of 3/8" Hose,
- (2) 25" H Jacks with 17" Stroke, 60 Ton Capacity, (2) 11" H Jacks with 8" Stroke, 60 Ton Capacity
- 30,000 lb. Line Pull Hydraulic Winch, 150' of Cable & Hook
- Front Bumper Storage Box
- 20 Ton Capacity Towing Package with 7 Prong Receptacle and Electric Brake Controller
- Triangle Reflector Kit & Fire Extinguisher (5 lb)
- Overall Height Decals on dash and on front of body
- Strobe Light
- Backup Alarm
- Weather Guard File Box Model 8878 mounted btw. bucket seats
- Spare Fuses Per CFR 395.95
- Weigh completed truck and install payload decal
- Safety prop for the truck hood to keep it from falling when open